

EDS-305/308/309/316 Series

5, 8, 9, and 16-port unmanaged Ethernet switches



- > Redundant dual 24 VDC power inputs
- > Relay output warning for power failure and port break alarm
- > Broadcast storm protection
- > Transparent transmission of VLAN tagged packets
- > -40 to 75°C operating temperature range (T models)



Introduction

The EDS-305/308/309/316 are 5, 8, 9, and 16-port Ethernet switches that provide an economical solution for your industrial Ethernet connections. The built-in relay warning function alerts network engineers when power failures or port breaks occur, and the switches are designed for harsh industrial environments, such as in hazardous locations (Class I, Div. 2/ATEX). The switches comply with FCC,

TÜV, UL, and CE standards, and come in two model types. Standard operating temperature range models (0 to 60°C) and wide operating temperature range models (-40 to 75°C). Both models undergo a 100% burn-in test to ensure that they fulfill the special needs of industrial automation control applications. The EDS-305/308/309/316 switches can be installed easily on a DIN-Rail or in a distribution box.

Specifications

Technology

Standards:

IEEE 802.3 for 10BaseT
 IEEE 802.3u for 100BaseT(X) and 100Base FX
 IEEE 802.3x for Flow Control

Processing Type: Store and Forward

Flow Control: IEEE 802.3x flow control, back pressure flow control

Interface

Fiber Ports: 100BaseFX ports (SC/ST connector)

RJ45 Ports: 10/100BaseT(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection

DIP Switches: Port break alarm mask

LED Indicators: PWR1, PWR2, FAULT, 10/100M (TP port), 100M (fiber port)

Alarm Contact: 1 relay output with current carrying capacity of 1 A @ 24 VDC

Optical Fiber

	100BaseFX		
	Multi-mode	Single-mode	Single-mode, 80 km
Wavelength	1300 nm	1310 nm	1550 nm
Max. TX	-10 dBm	0 dBm	0 dBm
Min. TX	-20 dBm	-5 dBm	-5 dBm
RX Sensitivity	-32 dBm	-34 dBm	-34 dBm
Link Budget	12 dB	29 dB	29 dB
Typical Distance	5 km, 2 km (EDS-316-T) ^a	40 km ^c	80 km ^d
	4 km, 2 km (EDS-316-T) ^b		
Saturation	-6 dBm	-3 dBm	-3 dBm

a. 50/125 μm, 800 MHz*km fiber optic cable
 b. 62.5/125 μm, 500 MHz*km fiber optic cable
 c. 9/125 μm single-mode fiber optic cable
 d. 9/125 μm single-mode fiber optic cable (80 km)

Power Requirements

Input Voltage:

EDS-305/308: 24 VDC (12 to 48 VDC), redundant inputs
 EDS-309/316: 24 VDC (12 to 45 VDC), redundant inputs

Input Current:

EDS-305: 0.13 A @ 24 V
 EDS-305-M/S: 0.17 A @ 24 V
 EDS-308: 0.13 A @ 24 V
 EDS-308-M/S: 0.21 A @ 24 V
 EDS-308-MM/SS: 0.26 A @ 24 V
 EDS-309-3M: 0.31 A @ 24 V
 EDS-316: 0.27 A @ 24 V
 EDS-316-M/S/MM/SS/MS: 0.44 A @ 24 V

Overload Current Protection:

EDS-305, EDS-305-M, EDS-305-S, EDS-308: 1.1 A
 EDS-308-M/S/MM/SS, EDS-309 series, EDS-316 series: 1.6 A

Connection: 1 removable 6-pin terminal blocks

Reverse Polarity Protection: Present

Physical Characteristics

Housing: Metal, IP30 protection

Dimensions:

EDS-305/308/309 Series:
 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)
 EDS-316 Series:
 80.5 x 135 x 105 mm (3.16 x 5.31 x 4.13 in)

Weight:

EDS-305/308/309 Series: 630 g
 EDS-316 Series: 1140 g

Installation: DIN-Rail mounting, wall mounting (with optional kit)

Ordering Information

Available Models		Port Interface				
Standard Temperature (0 to 60°C)	Wide Temperature (-40 to 75°C)	10/100BaseT(X)	100BaseFX			
			Multi-mode, SC Connector	Multi-mode, ST Connector	Single-mode, SC Connector	Single-mode, SC Connector, 80 km
EDS-305 Series						
EDS-305	EDS-305-T	5	---	---	---	---
EDS-305-M-SC	EDS-305-M-SC-T	4	1	---	---	---
EDS-305-M-ST	EDS-305-M-ST-T	4	---	1	---	---
EDS-305-S-SC	EDS-305-S-SC-T	4	---	---	1	---
EDS-305-S-SC-80	---	4	---	---	---	1
EDS-308 Series						
EDS-308	EDS-308-T	8	---	---	---	---
EDS-308-M-SC	EDS-308-M-SC-T	7	1	---	---	---
EDS-308-MM-SC	EDS-308-MM-SC-T	6	2	---	---	---
EDS-308-MM-ST	EDS-308-MM-ST-T	6	---	2	---	---
EDS-308-S-SC	EDS-308-S-SC-T	7	---	---	1	---
EDS-308-SS-SC	EDS-308-SS-SC-T	6	---	---	2	---
EDS-308-S-SC-80	EDS-308-S-SC-80-T	7	---	---	---	1
EDS-308-SS-SC-80	EDS-308-SS-SC-80-T	6	---	---	---	2
EDS-309 Series						
EDS-309-3M-SC	EDS-309-3M-SC-T	6	3	---	---	---
EDS-309-3M-ST	EDS-309-3M-ST-T	6	---	3	---	---
EDS-316 Series						
EDS-316	EDS-316-T	16	---	---	---	---
EDS-316-M-SC	EDS-316-M-SC-T	15	1	---	---	---
EDS-316-M-ST	EDS-316-M-ST-T	15	---	1	---	---
EDS-316-MM-SC	EDS-316-MM-SC-T	14	2	---	---	---
EDS-316-MM-ST	EDS-316-MM-ST-T	14	---	2	---	---
EDS-316-MS-SC	EDS-316-MS-SC-T	14	1	---	1	---
EDS-316-S-SC	EDS-316-S-SC-T	15	---	---	1	---
EDS-316-SS-SC	EDS-316-SS-SC-T	14	---	---	2	---
EDS-316-MS-SC-80	---	14	1	---	---	1
EDS-316-S-SC-80	---	15	---	---	---	1
EDS-316-SS-SC-80	---	14	---	---	---	2
EDS-316-SS-SC-40/80	---	14	---	---	1	1

Optional Accessories (can be purchased separately)

DR-4524/75-24/120-24: 45/75/120 W DIN-Rail 24 VDC power supplies

MDR-40-24/60-24: 40/60 W DIN-Rail 24 VDC power supplies, -20 to 70°C operating temperature

WK-46: Wall mounting kit

RK-4U: 4U-high 19" rack mounting kit